



Sélection des dômes

Caméras



Intérieur

Extérieur

Type	Caractéristiques	Caméra CCD Caméra IP/PoE	213 215	214	231D 232D	233D	VC-C4R VB-C10R	VB-C50i VC-C50i
	- Dôme suspendu, 10" - Fixation de plafond incluse - Fixation murale optionnelle	FB-1610-C FB-1610-S FB-1610-PC FB-1610-PS	FB-1610-50-C FB-1610-50-S	FB-1610-51-C FB-1610-51-S	Non-applicable	FB-1610-53-C FB-1610-53-S	FB-1610-50-C FB-1610-50-S	FB-1610-50-C FB-1610-50-S
	- Boîtier mural ou plafond, 9" - Dimensions 12" x 12" - Fixation intérieure pour caméra	FB-1609-C FB-1609-S FB-1609-PC FB-1609-PS	FB-1609-50-C FB-1609-50-S	FB-1609-51-C FB-1609-51-S	Non-applicable	FB-1609-53-C FB-1609-53-S	FB-1609-50-C FB-1609-50-S	FB-1609-50-C FB-1609-50-S
	- Dôme pour plafond suspendu - Fixation intérieure pour caméra - Plaque en plastique 2' x 2'	FBK1609-C FBK1609-S FBK1609-PC FBK1609-PS	FBK1609-50-C FBK1609-50-S	FBK1609-51-C FBK1609-51-S	Non-applicable	FBK1609-53-C FBK1609-53-S	FBK1609-50-C FBK1609-50-S	FBK1609-50-C FBK1609-50-S
	- Dôme suspendu, 12" - Construction en aluminium - Dôme en acrylique	FB-1612-C FB-1612-S FB-1612-PC FB-1612-PS	FB-1612-50-C FB-1612-50-S	FB-1612-51-C FB-1612-51-S	FB-1612-52-C FB-1612-52-S	FB-1612-53-C FB-1612-53-S	FB-1612-50-C FB-1612-50-S	FB-1612-50-C FB-1612-50-S
	- Dôme environnemental, 10" - Construction en ABS - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F	FB-3610-HB-C FB-3610-HB-S FB-3610-HB-PC FB-3610-HB-PS	FB-3610-50-HB-C FB-3610-50-HB-S	FB-3610-51-HB-C FB-3610-51-HB-S	Non-applicable	FB-3610-53-HB-C FB-3610-53-HB-S	FB-3610-50-HB-C FB-3610-50-HB-S	FB-3610-50-HB-C FB-3610-50-HB-S
	- Dôme environnemental, 12" - Construction en aluminium - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F	FB-3612-HB-C FB-3612-HB-S FB-3612-HB-PC FB-3612-HB-PS	FB-3612-50-HB-C FB-3612-50-HB-S	FB-3612-51-HB-C FB-3612-51-HB-S	FB-3612-52-HB-C FB-3612-52-HB-S	FB-3612-53-HB-C FB-3612-53-HB-S	FB-3612-50-HB-C FB-3612-50-HB-S	FB-3612-50-HB-C FB-3612-50-HB-S

























Sélection des dômes



interieur

exterieur

Type	Caractéristiques	OMNI360	PTC-400C	IQ-510 IQ-511	VN-C30U	WV-NS202	SCC-641	SCC-B9374
	- Dôme suspendu, 10" - Fixation de plafond incluse - Fixation murale optionnelle	FB-1610-100-C FB-1610-100-S	FB-1610-30-C FB-1610-30-S	FB-1610-110-C FB-1610-110-S	FB-1610-40-C FB-1610-40-S	FB-1610-81-C FB-1610-81-S	FB-1610-20-C FB-1610-20-S	FB-1610-21-C FB-1610-21-S
	- Boîtier mural ou plafond, 9" - Dimensions 12" x 12" - Fixation intérieure pour caméra	Non-applicable	FB-1609-30-C FB-1609-30-S	FB-1609-110-C FB-1609-110-S	FB-1609-40-C FB-1609-40-S	FB-1609-81-C FB-1609-81-S	FB-1609-20-C FB-1609-20-S	FB-1609-21-C FB-1609-21-S
	- Dôme pour plafond suspendu - Fixation intérieure pour caméra - Plaque en plastique 2' x 2'	Non-applicable	FBK1609-30-C FBK1609-30-S	FBK1609-110-C FBK1609-110-S	FBK1609-40-C FBK1609-40-S	FBK1609-81-C FBK1609-81-S	FBK1609-20-C FBK1609-20-S	FBK1609-21-C FBK1609-21-S
	- Dôme suspendu, 12" - Construction en aluminium - Dôme en acrylique	FB-1612-100-C FB-1612-100-S	FB-1612-30-C FB-1612-30-S	FB-1612-110-C FB-1612-110-S	FB-1612-40-C FB-1612-40-S	FB-1612-81-C FB-1612-81-S	FB-1612-20-C FB-1612-20-S	FB-1612-21-C FB-1612-21-S
	- Dôme environnemental, 10" - Construction en ABS - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F	FB-3610-100-HB-C FB-3610-100-HB-S	FB-3610-30-HB-C FB-3610-30-HB-S	FB-3610-110-HB-C FB-3610-110-HB-S	FB-3610-40-HB-C FB-3610-40-HB-S	FB-3610-81-HB-C FB-3610-81-HB-S	FB-3610-20-HB-C FB-3610-20-HB-S	FB-3610-21-HB-C FB-3610-21-HB-S
	- Dôme environnemental, 12" - Construction en aluminium - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F	FB-3612-100-HB-C FB-3612-100-HB-S	FB-3612-30-HB-C FB-3612-30-HB-S	FB-3612-110-HB-C FB-3612-110-HB-S	FB-3612-40-HB-C FB-3612-40-HB-S	FB-3612-81-HB-C FB-3612-81-HB-S	FB-3612-20-HB-C FB-3612-20-HB-S	FB-3612-21-HB-C FB-3612-21-HB-S

								
								
Type	Caractéristiques	VCC-9300 VCC-9400	EVI-D70	BRC-300	SNC-RZ25N	SNC-RX530 RX550 & RX570	SNC-RZ30 SNC-RZ50	IK-DP20A IK-DP30A
I n t é r i e u r	 <ul style="list-style-type: none"> - Dôme suspendu, 10" - Fixation de plafond incluse - Fixation murale optionnelle 	FB-1610-60-C FB-1610-60-S	FB-1610-70-C FB-1610-70-S	Non-applicable	FB-1610-73-C FB-1610-73-S	Non-applicable	FB-1610-75-C FB-1610-75-S	FB-1610-91-C FB-1610-91-S
	 <ul style="list-style-type: none"> - Boîtier mural ou plafond, 9" - Dimensions 12" x 12" - Fixation intérieure pour caméra 	Non-applicable	FB-1609-70-C FB-1609-70-S	Non-applicable	FB-1609-73-C FB-1609-73-S		FB-1609-75-C FB-1609-75-S	Non-applicable
	 <ul style="list-style-type: none"> - Dôme pour plafond suspendu - Fixation intérieure pour caméra - Plaque en plastique 2' x 2' 	FBK1609-60-C FBK1609-60-S	FBK1609-70-C FBK1609-70-S	Non-applicable	FBK1609-73-C FBK1609-73-S	Non-applicable	FBK1609-75-C FBK1609-75-S	FBK1609-91-C FBK1609-91-S
	 <ul style="list-style-type: none"> - Dôme suspendu, 12" - Construction en aluminium - Dôme en acrylique 	FB-1612-60-C FB-1612-60-S	FB-1612-70-C FB-1612-70-S	FB-1612-71-C FB-1612-71-S	FB-1612-73-C FB-1612-73-S	FB-1612-74-C FB-1612-74-S	FB-1612-75-C FB-1612-75-S	FB-1612-91-C FB-1612-91-S
r e c o n c e r t é	 <ul style="list-style-type: none"> - Dôme environnemental, 10" - Construction en ABS - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F 	FB-3610-60-HB-C FB-3610-60-HB-S	FB-3610-70-HB-C FB-3610-70-HB-S	Non-applicable	FB-3610-73-HB-C FB-3610-73-HB-S	Non-applicable	FB-3610-75-HB-C FB-3610-75-HB-S	FB-3610-91-HB-C FB-3610-91-HB-S
	 <ul style="list-style-type: none"> - Dôme environnemental, 12" - Construction en aluminium - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F 	FB-3612-60-HB-C FB-3612-60-HB-S	FB-3612-70-HB-C FB-3612-70-HB-S	FB-3612-71-HB-C FB-3612-71-HB-S	FB-3612-73-HB-C FB-3612-73-HB-S	FB-3612-74-HB-C FB-3612-74-HB-S	FB-3612-75-HB-C FB-3612-75-HB-S	FB-3612-91-HB-C FB-3612-91-HB-S



Sélection des dômes

TOSHIBA



TOSHIBA



TOSHIBA



interieur
exterieur

Type	Caractéristiques	IK-WB21A	IK-WB15A	IK-WR01A
	- Dôme suspendu, 10" - Fixation de plafond incluse - Fixation murale optionnelle	FB-1610-92-C FB-1610-92-S	FB-1610-93-C FB-1610-93-S	FB-1610-94-C FB-1610-94-S
	- Boîtier mural ou plafond, 9" - Dimensions 12" x 12" - Fixation intérieure pour caméra	FB-1609-92-C FB-1609-92-S	FB-1609-93-C FB-1609-93-S	FB-1609-94-C FB-1609-94-S
	- Dôme pour plafond suspendu - Fixation intérieure pour caméra - Plaque en plastique 2' x 2'	FBK1609-92-C FBK1609-92-S	FBK1609-93-C FBK1609-93-S	FBK1609-94-C FBK1609-94-S
	- Dôme suspendu, 12" - Construction en aluminium - Dôme en acrylique	FB-1612-92-C FB-1612-92-S	FB-1612-93-C FB-1612-93-S	FB-1612-94-C FB-1612-94-S
	- Dôme environnemental, 10" - Construction en ABS - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F	FB-3610-92-HB-C FB-3610-92-HB-S	FB-3610-93-HB-C FB-3610-93-HB-S	FB-3610-94-HB-C FB-3610-94-HB-S
	- Dôme environnemental, 12" - Construction en aluminium - Ventilation et chauffage inclus - Temp.: -30°C to +49°C -22°F to +120°F	FB-3612-92-HB-C FB-3612-92-HB-S	FB-3612-93-HB-C FB-3612-93-HB-S	FB-3612-94-HB-C FB-3612-94-HB-S

Téléphone: (800) 463-1455 (418) 286-6842
www.batko.com

Note:	C = Dôme clair	PC = Dôme opaque avec fenêtre claire
	S = Dôme fumé	PS = Dôme opaque avec fenêtre fumée